Application No.: 10/563,247 Docket No.: 29137.137.00

## **AMENDMENTS TO THE CLAIMS**

This listing of claims will replace all prior versions, and listings, of claims in the application.

## **Listing of Claims:**

- 1. (Currently Amended) A zirconia-alumina nano-composite powder formed of comprises sintered secondary particles prepared by sintering in nano-scale of from zirconia primary particles having a primary particle diameter of 10-50 nm and alumina primary particles having a primary particle diameter of 10-100 nm.
- 2. (Currently Amended) The zirconia-alumina nano-composite powder of claim 1, wherein a weight ratio of the zirconia <u>primary particles</u> to the alumina <u>primary particles</u> is in the range of 99.9:0.1 to 50:50.
- 3. (Currently Amended) The zirconia-alumina nano-composite powder of claim 1, further eontaining comprising an oxide of at least one metal selected from the group consisting of yttrium, magnesium, calcium, cerium, niobium, scandium, neodymium, plutonium, praseodymium, samarium, europium, gadolinium, promethium, and erbium.
- 4. (Currently Amended) The zirconia-alumina nano-composite powder of claim 3, wherein the molar ratio of the oxide of at least one metal to the zirconia <u>primary particles</u> is in the range of 0.0001:1 to 20:1.
- 5. (Withdrawn Currently Amended) A method of preparing the zirconia-alumina nano composite powder of claim 1, the method comprising: mixing a mixed solution of a polyhydric alcohol and a carboxylic acid and a mixed solution of a zirconium salt and an aluminum salt; heating the resulting mixture at 100-300 °C. to produce a polyester network structure where zirconium ions and aluminum ions are captured; and calcining the resulting polymer network structure at 400-1000 °C.

Application No.: 10/563,247 Docket No.: 29137.137.00

6. (Withdrawn) The method of claim 5, wherein the polyhydric alcohol is selected from the group consisting of ethyleneglycol, propyleneglycol, diethyleneglycol, triethyleneglycol, dipropyleneglycol, hexyleneglycol, butyleneglycol, glycerol, hydroquinone (p-dioxybenzene), catechol (1,2-dihydroxybenzene), resorcinol (resorcine or 1,3-dioxybenzene), pyrogallol (1,2,3-trihydroxybenzene), 5-hydroxymethylresorcinol (3,5-dihydroxybenzyl alcohol), phloroglucinol (1,3,5-trihydroxy benzene), and dihydroxybiphenol.

- 7. (Withdrawn) The method of claim 5, wherein the carboxylic acid is selected from the group consisting of a citric acid, a benzenetricarboxylic acid, a cyclopentatetracarboxylic acid, an adipic acid (1,4-butanedicarboxylic acid), a maleic acid (1,2-ethylenedicarboxylic acid), an oxalic acid, an succinic acid, a tartaric acid (dioxysuccinic acid), a mesaconic acid (methyl fumaric acid), a glutaric acid (n-pyrrotartaric acid), a malonic acid, a glycolic acid, a malic acid, a lactic cid, a gluconic acid, a fumaric acid, a phthalic acid (o-benzenedicarboxylic acid), an isophthalic acid (m-benzenedicarboxylic acid), a terephthalic acid, an m-hydroxybenzoic acid, a p-hydroxybenzoic acid, a salicylic acid (o-hydroxybenzoic acid), an itacnic acid (methylenesuccinic acid), a citraconic acid, an aconitic acid, a galic acid, a hydroxyethylehtylenediaminetriacetic acid (HEDTA), an ethyleneglycoltetraacetic acid (EGTA), an ethylenediaminetetrapionic acid.
- 8. (Withdrawn) The method of claim 5, wherein each of the zirconium salt and the aluminum salt is one of a chloride, a nitrate, and a hydroxide thereof.
- 9. (Withdrawn) The method of claim 5, wherein the mole ratio of the polyhydric alcohol and the carboxylic acid is in the range of 10:90 to 90:10.
- 10. (Withdrawn) The method of claim 5, wherein the mixed solution of a zirconium salt and an aluminum salt further comprises at least one metal salt selected from the group consisting of an yttrium salt, a magnesium salt, a calcium salt, a cerium salt, a cerium salt, a niobium salt, a scandium salt, a neodymium salt, a plutonium salt, a praseodymium salt, a samarium salt, an europium salt, a gadolinium salt, a promethium salt, and an erbium salt.

Application No.: 10/563,247 Docket No.: 29137.137.00

11. (Withdrawn) The method of claim 5, wherein the weight ratio of the zirconia-alumina nano-composite powder prepared using a zirconium salt and an aluminum salt to the mixed solution of a polyhydric alcohol and a carboxylic acid is in the range of 10:1 to 10:999.9.

12. (Withdrawn) A sintered zirconia-alumina composite obtained by sintering the zirconia-alumina nano-composite powder of any one of claims 1 through 4 at 1300 to 1500 °C.